

TECHNICAL DATA SHEET

Chassis Wash

1. Product Description

Chassis Wash is a powerful, water-based degreasing and cleaning solution designed specifically for undercarriage and chassis maintenance. It effectively removes accumulated mud, road salts, oil, grease, and grime to protect against corrosion and wear. Ideal for automotive, trucking, agricultural, and industrial vehicles.

2. Applications

- Undercarriage and chassis of cars, bakkies, trucks, and trailers
- Agricultural machinery and earth-moving equipment
- Vehicle fleets, buses, and off-road vehicles
- Suitable for use in workshops, truck wash bays, and maintenance depots

3. Product Features

- Heavy-duty cleaning action
- Water-based and biodegradable formula

- Safe on metal, rubber, plastic, and painted surfaces
- Helps reduce rust and corrosion by removing salt and grime
- Compatible with pressure washers and foam applicators
- Ideal for preventative maintenance

4. Typical Properties

Property	Specification
Appearance	Clear to slightly amber liquid
Fragrance	Mild industrial scent
pH (neat)	9.0 – 11.0
Density (25°C)	1.01 – 1.06 g/cm³
Solubility	Fully soluble in water
Foaming Level	Low to moderate



062 352 2368



thulekafactory@gmail.com



50 robyn street,
Jukskeipark



TECHNICAL DATA SHEET

5. Directions for Use

Manual Application:

1. Dilute **1:4 to 1:10** with water depending on soil level.
2. Apply to underside of vehicle using sprayer, mop, or brush.
3. Allow to sit for **5–10 minutes**. Do not allow to dry.
4. Rinse off thoroughly with high-pressure water.

Foam or Pressure Washer Use:

1. Pre-dilute 1:3 in a foaming applicator.
2. Spray onto the underside of vehicle.
3. Allow brief dwell time, then rinse with clean water.

Important: Ensure proper ventilation during use. Avoid contact with hot engine or exhaust parts.

6. Storage & Handling

- Store in original container in a cool, dry place
- Do not expose to extreme heat or freezing conditions
- Use gloves and eye protection when handling in bulk
- Keep out of reach of children

7. Packaging

Available in:

- 5L, 25L, and 200L HDPE containers
- Bulk packaging available on request

8. Safety & First Aid

- **Skin Contact:** Wash thoroughly with water and soap
- **Eye Contact:** Rinse immediately with clean water for 15 minutes
- **Ingestion:** Do not induce vomiting — seek medical attention



062 352 2368



thulekafactory@gmail.com



50 robyn street,
Jukskeipark

- **Inhalation:** Move to fresh air and seek help if irritation occurs

TECHNICAL DATA SHEET



062 352 2368



thulekafactory@gmail.com



50 robyn street,
Jukskeipark